

29. A method of repairing a light emitting device comprising a step of gradually changing a voltage applied to a light emitting element from a first voltage to a second voltage, wherein one of the first voltage and the second voltage is a ground voltage while the other is a reverse bias voltage.

5

30. A method according to claim 29, wherein the reverse bias voltage is within $\pm 15\%$ of an avalanche voltage of the light emitting element.

31. A method according to claim 29, wherein the light emitting element is an
10 electroluminescence element.

32. A method according to claim 29, wherein the light emitting device is included in an electric device selected from the group consisting of a video camera, a digital camera, a goggle type display, a head mounted display, a navigation system, an audio
15 reproducing device, a car audio, an audio component, a notebook computer, a game machine, a portable information terminal, a mobile computer, a cellular phone, a portable game machine, an electronic book, an image reproducing device, and a digital versatile disk (DVD) player.

20 33. A method of repairing a light emitting device comprising a step of:
applying a first voltage and a second voltage in order between an anode and a cathode of the light emitting device,

wherein the anode and the cathode are located in a light emitting element with a light emitting layer interposed therebetween, and

wherein the first voltage is a ground voltage while the second voltage is a reverse bias voltage.

34. A method according to claim 33, wherein the reverse bias voltage is within \pm
5 15% of an avalanche voltage of the light emitting element.

35. A method according to claim 33, wherein the light emitting element is an electroluminescence element.

36. A method according to claim 33, wherein the light emitting device is included
10 in an electric device selected from the group consisting of a video camera, a digital camera, a goggle type display, a head mounted display, a navigation system, an audio reproducing device, a car audio, an audio component, a notebook computer, a game machine, a portable information terminal, a mobile computer, a cellular phone, a portable
15 game machine, an electronic book, an image reproducing device, and a digital versatile disk (DVD) player.

37. A method of repairing a light emitting device comprising a step of:
gradually changing a voltage applied between an anode and an cathode of the
20 light emitting device from a first voltage to a second voltage,
wherein the anode and the cathode are located in a light emitting element with a light emitting layer interposed therebetween, and
wherein one of the first voltage and the second voltage is a ground voltage while the other is a reverse bias voltage.

38. A method according to claim 37, wherein the reverse bias voltage is within \pm 15% of an avalanche voltage of the light emitting element.

39. A method according to claim 37, wherein the light emitting element is an
5 electroluminescence element.

40. A method according to claim 37, wherein the light emitting device is included
in an electric device selected from the group consisting of a video camera, a digital
camera, a goggle type display, a head mounted display, a navigation system, an audio
10 reproducing device, a car audio, an audio component, a notebook computer, a game
machine, a portable information terminal, a mobile computer, a cellular phone, a portable
game machine, an electronic book, an image reproducing device, and a digital versatile
disk (DVD) player.

41. A method of repairing a light emitting device comprising a step of:
15

applying a first voltage and a second voltage in order between an anode and
a cathode of the light emitting device, thereby making a portion where a reverse-bias
current flows between the anode and the cathode insulating or highly resistive, and

wherein the anode and the cathode are located in a light emitting element with
20 a light emitting layer interposed therebetween, and

wherein the first voltage is a ground voltage while the second voltage is a
reverse bias voltage.

42. A method according to claim 41, wherein the reverse bias voltage is within \pm
25 15% of an avalanche voltage of the light emitting element.